


Complete range · Technical specifications

Machine Overview



built to perform

 **NEDSCHROEF**
MACHINERY

Headers

■ NH · NE series | 13 machine types

Machine type*	Unit	NHx12S	NHx12	NHx15	NHx15L	NHx18	NHx18L	NHx22M	NHx22L	NHx22EL	NH625	NHx30	NHx33M	NE524
Number of dies	/	5-6	5-6	5-6	5-6	5-6	5-6	5-6	5-6	5-6	6	5-6	5-6	5
Max. forging load	kN	800	800	1400 ¹	1400 ¹	2300	2300	2750 ²	2750 ²	2300	4000	5500	6500	3600
Cut-off diameter @ 600 N/mm ²	mm	12	12	17	17	20	20	22	22	22	28	30	36	27
Max. cut-off length	mm	90	125	150	162	170	190	190	250	310	305	265	265	247
Max. die kick-out	mm	65	100	125	135/140 ³	145	160	160	200	280	250	210	200	205
Speed	rpm	275	240	210	210	180	160	160	140	120/140 ⁴	120	105	90	105

* The x in a machine type is the number of stations. NHx12 is supplied as NH512 (5 stations) or NH612 (6 stations); the same applies to every type written with an x.

■ Selection Guide

Up to Ø22 mm - NHx12S to NHx22EL. Speed falls as diameter rises; the L and EL types trade speed for cut-off length and kick-out.

Ø27 mm and above - NE524, NH625, NHx30 and NHx33M, from 3600 to 6500 kN.

¹ Max. individual forging load per station limited to 650 kN.

² Forging load per station limited to 1150 kN.

³ 135 mm in the final station in case of a trimming operation installed.

⁴ 140 rpm for parts up to 200 mm, 120 rpm above 200 mm, to ensure stable part transfer.



built to perform

Boltmakers

■ NB · NEB series | 9 machine types


Machine type*	Unit	NBx12	NBx15	NBx15L	NBx18	NBx18L	NBx22M	NBx22L	NBx22EL	NEB524
Number of dies	/	5-6	5-6	5-6	5-6	5-6	5-6	5-6	5-6	5
Max. forging load	kN	800	1400 ¹	1400 ¹	2300	2300	2750 ²	2750 ²	2300	3600
Cut-off diameter @ 600 N/mm²	mm	12	17	17	20	20	22	22	22	27
Max. cut-off length	mm	125	150	162	170	190	190	250	310	247
Max. die kick-out	mm	100	125	135/140 ³	145	160	160	200	280	205
Speed ⁵	rpm	240	210	210	180	160	160	140	120/140 ⁴	105
Thread diameter	metric	M5-M10	M6-M12	M6-M12	M8-M16	M8-M16	M8-M20	M8-M20	M8-M20	M12-M24
Max. thread length	mm	80	100	100	120	120	135	135	135	95

* The x in a machine type is the number of stations. NHx12 is supplied as NH512 (5 stations) or NH612 (6 stations); the same applies to every type written with an x.

■ One cell, finished bolt

Every boltmaker combines the header with an integrated pointing and threading station. Thread range **M5 to M24**, thread length up to **135 mm**. Forming data matches the corresponding header type.

- ¹ Max. individual forging load per station limited to 650 kN.
- ² Forging load per station limited to 1150 kN.
- ³ 135 mm in the final station in case of a trimming operation installed.
- ⁴ 140 rpm for parts up to 200 mm, 120 rpm above 200 mm, to ensure stable part transfer.
- ⁵ Boltmaker speed depends on thread pitch and thread length.



built to perform

Ergonomic heavy-duty forming and complex parts

Nedmax ▪ Partformer

■ Nedmax NM series | 4 machine types

Machine type*	Unit	NMx28M	NMx28S	NMx33M	NMx33L
Number of dies	/	5-6	5-6	5-6	5-6
Max. forging load	kN	4000	4000	6500	6500
Cut-off diameter @ 600 N/mm ²	mm	28	28	36	36
Max. cut-off length	mm	265	165	250	375
Max. die kick-out	mm	210	125	200	310
Speed	rpm	115	115	90	80

* The x in a machine type is the number of stations (NMx33M → NM533M or NM633M).

■ Partformer NC714 | 7 dies

Machine type	Unit	NC714
Number of dies	/	7
Max. forging load	kN	800
Cut-off diameter @ 600 N/mm ²	mm	12
Max. cut-off length	mm	100
Max. die / kick-out	mm	100
Speed	rpm	160



built to perform

Nut formers

■ Cold nut formers MM series | 3 machine types

Machine type	Unit	MM8	MM12	MM16
Number of dies	/	5	5	5
Max. forging load	kN	1300	2200	3300
Product range	metric	M10 ⁶	M16 ⁶	M24 ⁶
Cut-off diameter @ 600 N/mm ²	mm	15	19	23
Cut-off length min – max	mm	5 - 19	7 - 25	8 - 35
Speed	rpm	250	200	150
WAF hex nuts min – max	mm	10 - 17	17 - 22	22 - 27
Max. product diameter	mm	21	26	36
Product height hex min – max	mm	5 - 19	6,5 - 22	7 - 35
Max. WAF square nuts	mm	13	18	24

■ Hot nut formers MW series | 3 machine types

Machine type	Unit	MW32	MW55	MW65
Number of dies	/	2	2	2
Max. forging load	kN	600	1300	2000
Product range	metric	M14-M22	M20-M36	M20-M42
Cut-off diameter @ 600 N/mm ²	mm	26	44	55
Cut-off length min – max	mm	12 - 44	14 - 65	22-80
Speed	rpm	180	150	100
WAF hex nuts min – max	mm	22 - 33	30 - 53	max. 65
Max. product diameter	mm	36	55	72
Product height hex min – max	mm	9 - 27	13 - 45	16 - 52
Max. WAF square nuts	mm	30	41	51

⁶ Product range depends on nut type. Stated for DIN 934 hex nuts; for flange nuts it depends on the flange diameter.

built to perform

Long stroke, straightening cutting and thread rolling

Cold headers ▪ Wire preparation ▪ Finishing

■ Cold headers | Long stroke BL series | 2 machine types

Machine type	Unit	BL2	BL4
Number of dies	/	4	4
Max. forging load	kN	800	1500
Cut-off diameter @ 600 N/mm ²	mm	12	16
Max. die kick-out	mm	200	300
Speed	rpm	150	90

■ Straightener RRA18 | 1 machine type

Machine type	Unit	RRA18
Min./max. product diameter	mm	6 / 20
Min./max. product length	mm	110 / 500
Maximum output	ppm	90
Floor space	m ²	1,5

■ Roll former NT60 | 1 machine type

Machine type	Unit	NT60
Thread diameter	metric	M30
Shaft length	mm	300
Thread length	mm	200
Die length	mm	406 / 381
Speed	ppm	120

■ Wire cutter NS16 | 1 machine type

Machine type	Unit	NS16
Wire diameter	mm	16
Min. / Max. cut-off length	mm	120 / 500
Speed	ppm	max. 260



built to perform

Contact

Let's talk about your next machine

Brigandstraat 10 | B-2200 Herentals | Belgium

+32 489 65 71 73 | sales@ned Schroef.be



built to perform

